

Appl. No. 09/989866

**AMENDMENT TO THE CLAIMS**

1.(currently amended): A service allocating device in a network where at least one first device which responds to a network service request transmitted by a user and at least one second device which does not respond to the network service request are connected and said second device having a setting of which can be modified from outside said second device ~~are connected~~, comprising:

a network information collecting section for obtaining information about a network service provided by the first device, responsive to the network service request, by communicating with said first device;

a setting device determining section for specifying the second device, which does not respond to the network service request, based on information from the network information collecting section;

a service mapping section for mapping network service parameters to be set into parameter values ~~[[of]]~~ corresponding to the second device specified by the setting device determining section; and

a service setting section for communicating with the second device and setting the parameter values obtained by the service mapping section in the second device,~~[[; which]]~~

thereby said service allocating device responds to the network service request by controlling the parameter values ~~performs control of the network service parameters of the~~ second device, allowing the second device to provide a network service corresponding ~~that does not correspond~~ to the network service provided by the first device, according to the network service request received by the first device.

**Appl. No. 09/989866**

2.(previously presented): The service allocating device according to claim 1, further comprising:

a service setting storing section storing setting contents of the first and second devices, which respond to previous network services; and

a service competition calculating section in checking a competition relation between network service requests from a plurality of users based on information stored in the service setting storing section, adjusting the competition relation, and determining the setting contents of the first and second devices so as to respond to the network service to be provided.

3.(previously presented): The service allocating device according to claim 1 further comprising:

a priority route selecting section selecting a device for providing a higher function of a requested network service, of the first and second devices which are connected to the network, and determining a communications route through which the selected devices are connected; and

a route comparison section communications route used prior to a new network service request with a communications route determined by the priority route selecting section.

4.(previously presented): The service allocating device according to claim 3, further comprising:

a route setting generating section determining communications route suitable for provision of the new network service based on a comparison result obtained by the route comparison section, which performs control so that the new network service can be provided, using a communications route determined by the route setting generating section.

Appl. No. 09/989866

~~BEST AVAILABLE COPY~~

5.(previously presented): The service allocating device according to claim 2, further comprising:

a service stoppage request generating section obtaining information about a network service provision state of the first device, detecting provision stoppage of a network service by the first device based on the network service provision state information, and generating a service stoppage request;

a service setting storing section storing a plurality of setting information of the first and second devices, which correspond to a network service that existed before provision stoppage of the network service is detected; and

a service competition calculating section calculating a service competition relation that is modified by the detected provision stoppage of the network service according to both the service stoppage request and storage information of the service setting storing section.

6.(currently amended): A service allocating method in a network where at least one first device which responds to a network service request transmitted by a user and at least one second device which does not respond to the network service request are connected and said second device having a setting of which can be modified from outside said second device, are connected, comprising:

- (a) obtaining information about a network service provided by the first device, responsive to the network service request, by communicating with said first device;
- (b) specifying the second device which does not respond to the network service request; [[and]]

**BEST AVAILABLE COPY**

Appl. No. 09/989866

(c) converting a setting content of the network service request received by the first device and requested for the first device, to ~~a setting content~~ parameters to which the second device can respond; and

(d) setting ~~a setting content~~ the parameters obtained by the conversion in the second device by communicating with the second device;

[[; which]] thereby responding to the network service request by controlling the parameter values performs control of the setting content of the second device, allowing the second device to provide a network service corresponding that does not correspond to the network service provided by the first device, according to the network service request received by the first device.

7.(original): The service allocating method according to claim 6, further comprising:

(e) storing setting contents of the first and second devices, which respond to previous network services; and

(f) checking a competition relation between network service requests from a plurality of users based on storage information in step (e), adjusting the competition relation and determining the setting contents of the first and second devices so as to respond to a network service to be provided.

8.(original): The service allocating method according to claim 6, further comprising:

(g) selecting a device for providing a higher function of a requested network service, of the first and second devices which are connected to the network, and determining a communications route through which the selected devices are connected; and

**Appl. No. 09/989866**

(h) comparing a communications route used prior to a new network service request with a communications route determined by the priority route selecting section.

9.(original): The service allocating method according to claim 8, further comprising:

(i) determining a communications route suitable for provision of the new network service based on a comparison result obtained by the route comparing section, which

performs control so that the new network service can be provided, using a communications route determined in step (i).

10.(original): The service allocating method according to claim 7, further comprising:

(j) obtaining information about a network service provision state of the first device, detecting provision stoppage of a network service by the first device based on the network service provision state information and generating a service stoppage request;

(k) storing a plurality of setting the first and second devices, which correspond to a network service existed that before provision stoppage of the network service is detected; and

(l) calculating a service competition relation that is modified by the detected provision stoppage of the network service according to both the service stoppage request and the information stored in step (e).

11.(currently amended): A computer-readable storage medium which stores a program for enabling a computer to execute a service allocating process in a network where at least one first device which responds to a network service request transmitted by a user and at least one

Appl. No. 09/989866

second device which does not respond to the network service request are connected and the second device having a [[the]] setting of which can be modified from outside the second device.  
~~are connected~~, the process comprising:

- (a) obtaining information about a network service provided by the first device,  
responsive to the network service request, by communicating with said first device;
  - (b) specifying the second device which does not respond to the network service  
request; [[and]]
  - (c) converting a setting content of the network service request received by the first  
device and requested for the first device to ~~a setting content~~ parameters to which the second  
device can respond; and
  - (d) setting ~~a setting content~~ the parameters obtained by the conversion in the second  
device by communicating with the second device;
- [[; which]] thereby responding to the network service request by controlling the  
parameter values performs control of the setting content of the second device, allowing the  
second device to provide a network service corresponding that does not correspond to the  
network service provided by the first device, according to the network service request received  
by the first device.

12.(original): The storage medium according to claim 11, the process further comprising:

- (e) storing setting contents of the first and second devices, which respond to previous  
network services; and
- (f) checking a competition relation between network service requests from a plurality  
of users based on information stored in step (e), adjusting the competition relation, and

**Appl. No. 09/989866**

determining the setting contents of the first and second devices so as to respond to a network service to be provided.

13.(original): The storage medium according to claim 11, the process further comprising:

(g) selecting a device for providing a higher function of a requested network service, of the first and second devices which are connected to the network, and determining a communications route through which the selected devices are connected; and

(h) comparing a communications route used prior to a new network service request with a communications route determined by the priority route selecting section.

14.(original): The storage medium according to claim 13, the process further comprising:

(i) determining a communications route suitable for provision of the new network service based on a comparison result obtained by the route comparing section, which

performs control so that the new network service can be provided, using a communications route determined in step (i) .

15.(original): The storage medium according to claim 12, the process further comprising:

(j) obtaining information about a network service provision state of the first device, detecting provision stoppage of a network service by the first device based on the network service provision state information, and generating a service stoppage request;

Appl. No. 09/989866 **BEST AVAILABLE COPY**

(k) storing a plurality of setting information of the first and second devices, which correspond to a network service before provision stoppage of the network service is detected; and

(l) calculating a service competition relation that is modified by the detected provision stoppage of the network service, according to both the service stoppage request and the information stored in step (e).